



LEGEND


- Input
- △ AC
- DC CC
- Output
- DC CV
- 0-10V
- Auxiliary Signal
- ▬ Ethernet
- ✕ DMX
- ⤿ Wireless Signal
- Ⓜ Bluetooth




C-T1C-24-DS00
 SINGLE CH 0-10V CONTROLLER
 3.25"x1.5"x0.25" (83x38x6.4mm)
 INPUT 12-24 VDC | OUTPUT 0-10VDC
 0-10V DIMMING 100mA MAX
 INSTALL WITHIN 60' OF CLOSEST DEVICE




C-400
 C-400-12-DS00
 RS485 CONTROLLER
 FOREST DRAPERY PROTOCOL COMPATIBLE
 3.5"x1.7"x1.4" (90x44x35mm)
 POWER INPUT 5VDC TO 30VDC | INDOOR USE ONLY
 INSTALL WITHIN 60' OF CLOSEST DEVICE




C-T1C-11
 C-T1C-11-DL00
 SINGLE CH 0-10V CONTROLLER WITH RELAY
 5.25"x1.5"x1.125" (134x38x29mm)
 AC INPUT 110-277VAC
 OUTPUT RELAY 110-277VAC | 10 AMPS MAX
 0-10V DIMMING 100mA MAX
 INSTALL WITHIN 60' OF CLOSEST DEVICE




CF
 C-F00-11-DL00
 FORWARD PHASE DIMMING CONTROLLER
 5.25"x1.5"x1.25" (134x38x29mm)
 LINE INPUT 100-277VAC
 200W MAX | AUXILIARY +24VC OUTPUT 100mA
 INSTALL WITHIN 60' OF CLOSEST DEVICE




CR
 C-R00-11-DL00
 REVERSE PHASE CONTROLLER
 5.25"x1.5"x1.25" (134x38x29mm)
 LINE INPUT 100-277VAC
 200W MAX | AUXILIARY +24VC OUTPUT 100mA
 INSTALL WITHIN 60' OF CLOSEST DEVICE




CT20
 C-T20-17-DJ00
 LOAD CONTROLLER 0-10V 20A
 3.25"x2.17"x1.22" (83x55x31mm)
 LINE INPUT 100-277VAC | OUTPUT 100-277VAC
 INSTALL WITHIN 60' OF CLOSEST DEVICE



CX51
 C-X51-24-DS00
 DMX CONTROLLER
 2.2" x 1.2" x 0.7" (72.6 x 30.0 x 18.0 mm)
 INPUT 12-24 VDC | OUTPUT 12-24 VDC
 INSTALL WITHIN 60' OF CLOSEST DEVICE




CT2C
 C-T2C-24-DS00
 DUAL CH, 0-10V TUNABLE WHITE CONTROLLER
 3.25"x1.5"x0.875" (82.5x38x22mm)
 INPUT 12-24 VDC | OUTPUT 0-10VDCx2CH
 INSTALL WITHIN 60' OF CLOSEST DEVICE




CB1S
 C-B1S-24-DS00
 BEAM SHAPER CONTROLLER
 3.25"x1.7"x1.36" (90x43.2x34.5mm)
 INPUT 24 VDC | OUTPUT 4 PIN ZOOM LENS
 INSTALL WITHIN 60' OF CLOSEST DEVICE



CS1C
 C-S1C-24-DS00
 SENSOR/DRY-CONTACT CONTROLLER
 3.25"x1.5"x0.25" (82.5x38x6.35mm)
 INPUT 12-24 VDC | OUTPUT 0-10VDC
 INSTALL WITHIN 60' OF CLOSEST DEVICE



XSF
 X-SF-024-DS00
 SUPERFRIEND CONTACT CONTROLLER
 3.25"x1.5"x0.25" (82.5x38x6.35mm)
 INPUT 12-24 VDC | OUTPUT 0-10VDC
 INSTALL WITHIN 60' OF CLOSEST DEVICE



CX4C
 C-X4C-24-DS00
 DMX CONTROLLER
 2.2"x1.2"x0.7" (72.6x30x18mm)
 INPUT 12-24 VDC | OUTPUT 0-10VDC
 INSTALL WITHIN 60' OF CLOSEST DEVICE

LEGEND

- Input
- △ AC
- DC CC
- Output
- DC CV
- 0-10V
- Auxiliary Signal
- || Ethernet
- ↔ Wireless Signal
- Bluetooth
- WiFi
- BC BubblyNet Cloud

T4

T-T04-24-DWH0
T4 TOUCHSCREEN
5.6"x4.3"x2.6" (143x109x66MM)
INPUT 5V

110V PLUG-IN TRANSFORMER INCLUDED
INSTALL WITHIN 60' OF CLOSEST DEVICE

G4

T-G04-24-DWH0
G4 TOUCHSCREEN
5.6"x4.3"x2.6" (143x109x66MM)
INPUT 5V

110V PLUG-IN TRANSFORMER INCLUDED
INSTALL WITHIN 60' OF CLOSEST DEVICE

T4S

T-T04-24-SWH0
T4S TOUCHSCREEN
5.3"x4.0"x1.6" (134x102x41MM)
INPUT 5V

REQUIRES MICRO USB + HDMI
INSTALL WITHIN 60' OF CLOSEST DEVICE

G4S

T-G04-24-SWH0
G4S TOUCHSCREEN
5.3"x4.0"x1.6" (134x102x41MM)
INPUT 5V

REQUIRES MICRO USB + HDMI
INSTALL WITHIN 60' OF CLOSEST DEVICE

T7

T-T07-24-DWH0
T7 TOUCHSCREEN
8.2"x5.4"x2.3" (208x138x59MM)
INPUT 5V

110V PLUG-IN TRANSFORMER INCLUDED
INSTALL WITHIN 60' OF CLOSEST DEVICE


G7

T-G07-24-DWH0
G7 TOUCHSCREEN
8.2"x5.4"x2.3" (208x138x59MM)
INPUT 5V

110V PLUG-IN TRANSFORMER INCLUDED
INSTALL WITHIN 60' OF CLOSEST DEVICE

LEGEND

- Input
- △ AC
- DC CC
- ➔ Output
- DC CV
- 0-10V
- Auxiliary Signal
- ▬ Ethernet
- ⚡ Wireless Signal
- Ⓜ Bluetooth



KC3

K-C3-UDS-00WH / WALL MOUNT
F-U1-MWH FACE PLATE
KEYPAD SWITCH + PIR OCC SENSOR
4.5"x2.75"x.75" (114x70x19mm)
INPUT 110-277VAC
INSTALL WITHIN 60' OF CLOSEST DEVICE

SOCW

S-OC-W24-DT00
DUAL-TECH WALL OCC SENSOR
PIR + HIGH FREQUENCY DOPPLER
SURFACE WALL OR CEILING MOUNT
4.4"x2.6"x1.8" (112x66x46mm)
INPUT 24VDC
INSTALL WITHIN 60' OF CLOSEST DEVICE

SCO

S-CO-C24-DRWH
CO2 SENSOR
3.0" (76.2MM) DIAMETER
RECESS CEILING MOUNT / 10FT (3m)
INPUT 24VDC
INSTALL WITHIN 60' OF CLOSEST DEVICE

SOP

S-OP-C12-DRWH
OCC + PHOTOCELL PIR SENSOR + PHOTOCELL
2.68" (68MM) DIAMETER
RECESS CEILING MOUNT / 10FT (3m)
INPUT 24VDC
INSTALL WITHIN 60' OF CLOSEST DEVICE

SDL

S-DL-C12-DRWH
DAYLIGHT + OCC PIR SENSOR
3.66" (93MM) DIAMETER
RECESS CEILING MOUNT / 10FT (3m)
INPUT 24VDC
INSTALL WITHIN 60' OF CLOSEST DEVICE

SODC

S-OD-C24-DR00
DUAL TECH CEILING MOUNTED SENSOR
4.52" (114.808MM) DIAMETER
RECESS CEILING MOUNT / 10FT (3m)
INPUT 24VDC
INSTALL WITHIN 60' OF CLOSEST DEVICE

SOPH

S-OP-H12-D000
HIGH BAY + PIR OCC SENSOR PHOTOCELL
3.66" (93MM) DIAMETER
SURFACE CEILING MOUNT / UP TO 40FT (12.2m)
INPUT 24VDC
INSTALL WITHIN 60' OF CLOSEST DEVICE

SOPL

S-OP-L12-D000
LOW BAY + PIR OCC SENSOR PHOTOCELL
3.66" (93MM) DIAMETER
SURFACE CEILING MOUNT / UP TO 30FT (9.1m)
INPUT 24VDC
INSTALL WITHIN 60' OF CLOSEST DEVICE

SMP

S-MP-W03-DT00
MAGNETIC CONTACT SENSOR
2.6"x1.6"x.6" (65x40x15mm)
3V COIN BATTERY OPERATED
INSTALL WITHIN 60' OF CLOSEST DEVICE

SAQ

S-AQ-W26-DWWH
AIR QUALITY SENSOR
3.3"x1.5"x0.65" (83x38x17mm)
INPUT 24VDC
INSTALL WITHIN 60' OF CLOSEST DEVICE

SDLK

S-DL-K17-DKWH
DAYLIGHT OCC PIR SENSOR
2.5"x4.7" (64x119mm)
TRACK MOUNTED
INPUT 110-277VAC
INSTALL WITHIN 60' OF CLOSEST DEVICE

SOPK

S-OP-K17-DKWH
OCC + PHOTOCELL
2.5"x4.7" (64x119mm)
TRACK MOUNTED
INPUT 110-277VAC
INSTALL WITHIN 60' OF CLOSEST DEVICE

LEGEND

- Input
- △ AC
- DC CC
- Output
- DC CV
- 0-10V
- Auxiliary Signal
- ▬ Ethernet
- ↔ Wireless Signal
- Ⓜ Bluetooth

KQ1B

K-Q1-UDB-00WH
F-U1-MWH FACEPLATE
1 BTN BATTERY Q SERIES KEYPAD
3.17" x 4.97" x 0.26"
(80.5 x 126.24 x 6.6 mm)
INSTALL WITHIN 60' OF CLOSEST NON BATTERY DEVICE

KQ2B

K-Q2-UDB-00WH
F-U1-MWH FACEPLATE
2 BTN BATTERY Q SERIES KEYPAD
3.17" x 4.97" x 0.26"
(80.5 x 126.24 x 6.6 mm)
INSTALL WITHIN 60' OF CLOSEST NON BATTERY DEVICE

KQ3B

K-Q3-UDB-00WH
F-U1-MWH FACEPLATE
3 BTN BATTERY Q-KEYPAD
3.17" x 4.97" x 0.26"
(80.5 x 126.24 x 6.6 mm)
INSTALL WITHIN 60' OF CLOSEST NON BATTERY DEVICE

KQ4B

K-Q4-UDB-00WH
F-U1-MWH FACEPLATE
4 BTN BATTERY Q-KEYPAD
3.17" x 4.97" x 0.26"
(80.5 x 126.24 x 6.6 mm)
INSTALL WITHIN 60' OF CLOSEST NON BATTERY DEVICE

KQ1W

K-Q1-UDW-00WH
F-U1-MWH FACEPLATE
1 BTN LOW VOLT Q-KEYPAD
3.17" x 4.97" x 0.26"
(80.5 x 126.24 x 6.6 mm)
INSTALL WITHIN 60' OF CLOSEST DEVICE

KQ2W

K-Q2-UDW-00WH
F-U1-MWH FACEPLATE
2 BTN LOW VOLT Q-KEYPAD
3.17" x 4.97" x 0.26"
(80.5 x 126.24 x 6.6 mm)
INSTALL WITHIN 60' OF CLOSEST DEVICE

KQ3W

K-Q3-UDW-00WH
F-U1-MWH FACEPLATE
3 BTN LOW VOLT Q-KEYPAD
3.17" x 4.97" x 0.26"
(80.5 x 126.24 x 6.6 mm)
INSTALL WITHIN 60' OF CLOSEST DEVICE

KQ4W

K-Q4-UDW-00WH
F-U1-MWH FACEPLATE
4 BTN LOW VOLT Q-KEYPAD
3.17" x 4.97" x 0.26"
(80.5 x 126.24 x 6.6 mm)
INSTALL WITHIN 60' OF CLOSEST DEVICE

KQ1L

K-Q1-UDL-00WH
F-U1-MWH FACEPLATE
1 BTN LINE-VOLT Q-KEYPAD
3.17" x 4.97" x 0.26"
(80.5 x 126.24 x 6.6 mm)
INSTALL WITHIN 60' OF CLOSEST DEVICE

KQ2L

K-Q2-UDL-00WH
F-U1-MWH FACEPLATE
2 BTN LINE-VOLT Q-KEYPAD
3.17" x 4.97" x 0.26"
(80.5 x 126.24 x 6.6 mm)
INSTALL WITHIN 60' OF CLOSEST DEVICE

KQ3L

K-Q3-UDL-00WH
F-U1-MWH FACEPLATE
3 BTN LINE-VOLT Q-KEYPAD
3.17" x 4.97" x 0.26"
(80.5 x 126.24 x 6.6 mm)
INSTALL WITHIN 60' OF CLOSEST DEVICE

KQ4L

K-Q4-UDL-00WH
F-U1-MWH FACEPLATE
4 BTN LINE-VOLT Q-KEYPAD
3.17" x 4.97" x 0.26"
(80.5 x 126.24 x 6.6 mm)
INSTALL WITHIN 60' OF CLOSEST DEVICE

KC3


K-C3-UDS-00WH / WALL MOUNT
F-U1-MWH FACE PLATE
KEYPAD SWITCH + PIR OCC SENSOR
4.5"x2.75"x.75" (114x70x19mm)
INPUT 110-277VAC
INSTALL WITHIN 60' OF CLOSEST DEVICE

LEGEND


- Input
- △ AC
- DC CC
- ➔ Output
- DC CV
- 0-10V
- Auxiliary Signal
- ▬ Ethernet
- ⚡ Wireless Signal
- Ⓜ Bluetooth




D-C11
D-C11-03-18-17-D000
18W MAX CONST CURR DRIVER
3.5"x1.7"x1.4" (90x43x34.5mm)
INPUT 110-277VAC | OUTPUT 3-18VDC
OUT CURR 1,000mA MAX
INSTALL WITHIN 60' OF CLOSEST DEVICE




D-C70
D-C70-30-42-17-D000
26W MAX CONST CURR DRIVER
3.5"x1.7"x1.4" (90x43x34.5mm)
INPUT 110-277VAC | OUTPUT 30-42VDC
OUT CURR 700mA MAX
INSTALL WITHIN 60' OF CLOSEST DEVICE




D-V1K
D-V1K-00-24-17-D000
25W MAX CONST VOLT DRIVER
3.5"x1.7"x1.4" (90x43x34.5mm)
INPUT 110-277VAC | OUTPUT 24VDC
OUT CURR 1,000mA MAX
INSTALL WITHIN 60' OF CLOSEST DEVICE




D-B70
D-B70-30-42-17-D000
DUAL CH TUNABLE WHITE CONST CURR DRIVER
4.25"x1.7"x1.25" (108x43x32mm)
INPUT 110-277VAC | OUTPUT 30-42VDC
MAX AC INPUT CURR 0.4A
MAX DC OUT CURR 700mA MAX (2 CHANNEL COMBINED)
INSTALL WITHIN 60' OF CLOSEST DEVICE




D-C1K
D-C1K-30-42-17-D000
42W MAX CONST CURR DRIVER
3.5"x1.7"x1.4" (90x43x34.5mm)
INPUT 110-277VAC | OUTPUT 30-42VDC
OUT CURR 1,000mA MAX
INSTALL WITHIN 60' OF CLOSEST DEVICE




D-B1K
D-B1K-30-42-17-DL00
42W MAX CONST CURR DRIVER
4.25"x1.7"x1.25" (108x43x32mm)
INPUT 110-277VAC | OUTPUT 30-42VDC
OUT CURR 1,000mA MAX
INSTALL WITHIN 60' OF CLOSEST DEVICE



D-V2K
D-V2K-00-48-17-DL00
96W MAX CONST VOLT DRIVER
7.5"x2.125"x1.5" (191x54x38mm)
INPUT 110-277VAC | OUTPUT 48VDC
OUT CURR 2,000mA MAX
INSTALL WITHIN 60' OF CLOSEST DEVICE




D-D4K
D-D4K-00-24-17-DL00
96W MAX 2 CH CONST VOLT DRIVER
7.5"x2.125"x1.5" (191x54x38mm)
INPUT 110-277VAC | OUTPUT 24VDC 2CH
OUT CURR 4,000mA MAX
INSTALL WITHIN 60' OF CLOSEST DEVICE



D-V4K
D-V4K-00-24-17-DL00
96W MAX SINGLE CH CONST VOLT DRIVER
7.5"x2.125"x1.5" (191x54x38mm)
INPUT 110-277VAC | OUTPUT 24VDC
OUT CURR 4,000mA MAX
INSTALL WITHIN 60' OF CLOSEST DEVICE



D-F70
D-F70-07-20-24-D000
RGBW / 4 CH CONST CURR DRIVER
4"x1.75"x1.125" (102x44.5x29mm)
INPUT 24VAC | OUTPUT 7-20VDC
MAX AC INPUT CURR 3A
MAX DC OUT CURR 700mA MAX (PER CHANNEL)
INSTALL WITHIN 60' OF CLOSEST DEVICE



D-G4K
D-G4K-00-24-DL00
RGBW / 4 CH CONST VOLT DRIVER
5.1"x1.75"x1.125" (129.2x44.5x29mm)
INPUT 24VDC | OUTPUT 7-20VDC
MAX AC INPUT CURR 3A
MAX DC OUT CURR 700mA MAX (PER CHANNEL)
INSTALL WITHIN 60' OF CLOSEST DEVICE

LEGEND

- Input
- △ AC
- DC CC
- Output
- DC CV
- 0-10V
- Auxiliary Signal
- || Ethernet
- ↔ Wireless Signal
- Bluetooth
- WiFi
- BC BubblyNet Cloud

